Pump Out System for Sullage **Disposal on Non-sewered Sites**



Plumbing Permit Number	Guidelines
PD Owners Details	The following Guidelines are required to be complied with for the below ground dispersion of sullage waste (ie. Liquid wastes not polluted by human waste).
Title: I Mr I Mrs I Ms I Miss	Location
Given name(s) Surname	 Under no circumstances shall effluent be allowed to discharge above ground or onto adjoining properties. The effluent shall be pumped to approved below ground disposal trenches.
Residential address	Mechanical System
Suburb Postcode Phone (W) (H) Mobile Email address	 Sullage shall be disposed of to a 450 litre holding tank designed to permit maximum pump out via an automatic motor and pump. The pump shall commence operation before the stored volume exceeds 120 litres Pump motor is to be connected to electricity via an underground connection if not adjacent to a building Maintenance of the pump out system is the responsibility of the owner and occupier
Owners Signature(s)	Sullage Quality
Site address Site address Suburb Postcode Lot number Plan number	 The system shall be used to accept waste not polluted by human wastes. Inputs to the system shall not include the human waste from the following: Residues from stained nappies or nappy cleaning systems To ensure that the above requirements are met, you would be required to submit an application form and supply details relating to the type of pump. Where installations are to be located adjacent to adjoining
Features Site area	properties or dwelling, the provisions of a Sound Insulation Enclosure may be required.
Image: Site area Image: Site area	Office Use Only Approval is hereby issued for the installation of a permanent watering system in accordance with the attached plans.
Dishwasher Bath Laundry tub Vanity Other: (Specify)	Comments
Physical System	Technical Officer
Pump type Head Pressure Size of discharge hose Length Where installations are to be located adjacent to adjoining properties or	Technical Officer Fee paid \$ CSC Receipt Date

dwellings the provision of a Sound Insulation Enclosure may be required.

astes not polluted by human waste). Location

- Under no circumstances shall effluent be allowed to discharge above ground or onto adjoining properties.
- The effluent shall be pumped to approved below ground disposal trenches.

Mechanical System

- Sullage shall be disposed of to a 450 litre holding tank designed to permit maximum pump out via an automatic motor and pump.
- The pump shall commence operation before the stored volume exceeds 120 litres
- Pump motor is to be connected to electricity via an underground connection if not adjacent to a building
- Maintenance of the pump out system is the responsibility of the owner and occupier

Sullage Quality

- The system shall be used to accept waste not polluted by human wastes.
- Inputs to the system shall not include the human waste from the following:
 - Residues from stained nappies or nappy cleaning systems

Office Use Only

Approval is hereby issued for the installation of a permanent watering
system in accordance with the attached plans.

CSBPS014 - 05/01/2015

Information Privacy Act 2009 - Redland City Council is collecting your personal information in order to process this application. The information will only be used by authorised Council Officers for the purpose of a pump-out system for sullage disposal on non-sewered sites and ensuring our records are accurate. Your information will not be given to any other person or agency unless you have given us permission or we are required by law to do so.

Redland City Council PO Box 21 Cleveland QLD 4163 | T 07 3829 8999 | F 07 3829 8765 | E rcc@redland.qld.gov.au | W www.redland.qld.gov.au